

## 0896 CREATIVO TOP WHITE

### METHOD STATEMENT FOR APPLICATION ON WALLS

#### SURFACE PREPARATION:

Surfaces need to be compact, sound, dry, solid, clean, free from dust, grease, oil, waxes, sealers, silicone compounds or any other item that might affect adhesion of the system.

Old paint, not perfectly compact and adherent to the substrate, needs to be removed.

Sterilize contaminations of moulds, fungi and algae with **MUROSANO RISANANTE**, disinfectant for restoration of surfaces contaminated by moulds and algae

Missing parts, holes, cracks or damages, need to be repaired with specific restoration mortars. The repaired areas should be cured correctly according to the nature of the thickness and product applied.

#### APPLICATION:

##### PRIMER A:

Application of **PRIMER A**, acrylic water-based, impregnating and reinforcing primer. to consolidate the surface and balance absorption rate. Dilute **PRIMER A** with water in a 1:4 ratio. Mix it accurately and apply by brush, roller or airless, saturating the whole surface. Use product at a room temperature between and treated surface between 8°C and 35°C. Relative humidity should not exceed 75%. Wait at least 4-5 hours to apply subsequent coat.

##### CREATIVO TOP WHITE:

Mix carefully **COMPONENT A** before use, add **COMPONENT B (1.25 kg of COMPONENT A with 0.2 kg of COMPONENT B)**, drums are packaged accordingly to this ratio), mix well and apply with specific **CREATIVO® MOHAIR ROLLER** taking care of applying homogeneously the product without leaving deposit. First coat can be diluted up to 10% with water. Material pot life is 1 hour maximum, do not use the product after if time exceeded the limit. After about 6 hours, and not later than 24 hours from the first coat, apply a second one with the same method, diluting 0-5% with water. In case over 24 hours have passed, it is necessary to sand the surface with thin grit sandpaper (250G and over) and vacuum before proceeding to the next coat. When protecting areas with water stagnation, it is necessary to apply a third coat of **CREATIVO® TOP**.

Wash well the tools with water after use.

**CREATIVO TOP** is dry after 24 hours. After 3-4 days it achieves greater resistances. 80% of its chemical and physical resistances are reached after 72 hours, for complete hardening and performances wait 7 days. Environment temperatures and humidity can affect drying and filming times. Do not wash the surface before 7 days from application. Do not expose to dust, vapor, oil, grease or liquid substances before 7 days from application of the last coat.

#### CLEANING AND MAINTENANCE:

Clean the surface with neutral detergents. Do not use a vapour steam cleaner.

It is possible to use cleaning machines for professional use only if without abrasive brushes.

Wait 7 days before cleaning the surface for the first time.

Remove any aggressive substance from surface trying to avoid prolonged contact as it might affect the finish.

Avoid direct contact of high heat items (pots and pans).

Touch ups can be easily performed by sanding and vacuuming the surface before activity.

**CREATIVO® IS A BRAND OF  
Colorificio MP S.r.l.**

Via G.Pastore, 2 (Z.A. Viserba) 47922 – Rimini (Italia)  
Tel. +39 0541 734086 Fax +39 0541 734282

[mp@colorificiomp.it](mailto:mp@colorificiomp.it) - [www.creativo-microcemento.it](http://www.creativo-microcemento.it) - [www.creativo-microcemento.com](http://www.creativo-microcemento.com)

**IMPORTANT NOTES:**

- Before application, ensure that the surface is perfectly dry and hardened, and that it has good adherence to the substrate. It must be clean and free from oil, grease, mould, fungus, bacteria, efflorescence or any other defect that could impair adherence or successful results.
- Protect containers from freezing temperatures (minimum + 5° C).
- Store in a cool, dry place; do not expose to direct sunlight.
- The temperature of both the work environment and substrate should be between + 8° C and + 30° C. Relative humidity must not exceed 75%.
- Avoid curing with temperatures of environments and substrate below +5°C.
- Arrange the scaffolds in such a way as to allow continuous application until architectural interruptions to avoid the formation of joints, overflows and colour differences.
- Obtain enough of the colour in a single batch to complete the job or at least complete portions of work which do not draw attention to shade differences.
- Due to the complexity of the system and its possible application, please contact our Technical Team for any clarification.

**CREATIVO® IS A BRAND OF  
Colorificio MP S.r.l.**

Via G.Pastore, 2 (Z.A. Viserba) 47922 – Rimini (Italia)  
Tel. +39 0541 734086 Fax +39 0541 734282

[mp@colorificiomp.it](mailto:mp@colorificiomp.it) - [www.creativo-microcemento.it](http://www.creativo-microcemento.it) - [www.creativo-microcement.com](http://www.creativo-microcement.com)