



TdS: Art. 0857 **ANTICA PATINATURA (Gold Rev. 1.1 / Perla 2.2)**

Date of update 08/05/2015

Acrylic paste for artistic finish effects for interior use. Mould resistant formula

CHARACTERISTICS:

ANTICA PATINATURA is an acrylic decorative paste, protective and water-repellent, used to create artistic decorative effects on indoor surfaces. Formulated with acrylic resins and iridescent pigments, it consists of a thick paste that once spread out on a surface it appears as a smooth silky finish, that protects from grease and dirt. When applied on textured surfaces it increases the depth of the finish effect. Mould resistant formula

USES:

Paste used as a finish, for interior use, protective hydrophobic, can be used on paints, lime based venetian plasters, mineral lime based or silicate plasters. It can also be applied on synthetic emulsion paints as long as they are absorbent, not flaking and well anchored to the support.

PREPARATION AND APPLICATION:

To obtain the best results, application is best made on surfaces prepared with: **COCCIO ANTICO TRAVERTINO** Effect, **RILIEVI**, trowelled or smoothed **MARMO DI VENEZIA**®, smoothed **INTONANTICO**, **RASATO FINE**, **RASATO TRAVERTINO**, **ACCADEMIA STRUCTUR**, **MURO ANTICO**.

On a perfectly dry support, apply a very thin coat of **ANTICA PATINATURA** using a stainless-steel trowel or spatula, or a sponge or fur glove, passing over the area energetically with the tool used in order to prevent accumulating the product in the same place and ensure uniform application.

The product can be applied with a circular movement or with crossed strokes, depending on the desired decorative effect; by overlapping different or contrasting colours and nuances it's possible to create endless decorative effects depending only on the decorator's imagination.

IMPORTANT NOTES:

- **Before applying, make sure the support is perfectly dry and cured and perfectly anchored to the substratum, that it is not dirty, greasy, contaminated with mildew, fungi, bacteria, salts or anything else likely to prevent good adhesion and a successful result.**
- **Protect packaging from frost (minimum + 5°C)**
- **Store in a cool, dry place away from sunlight.**
- **Use the product at room and support temperature between + 8°C and + 35°C and with relative humidity not above 75%**
- **Avoid drying at room or support temperatures below + 5°C**
- **Wash tools with water after use.**
- **Do not expose the treated surfaces to washing with water as the product will become soluble and be washed away**

TECHNICAL DATA:

DILUTION	Ready to use
APPEARANCE OF DRY FINISH	Silky pearlescent soft texture
CONSUMPTION	0.050 - 0.070 l/m ²
DENSITY (UNI EN ISO 2811-1:2003)	1,00 ± 0.05 kg/l
pH	~ 8,5 ± 1
DRYING TIME AT 20°C	Dust dry 2 hours, in depth 12-24 hours.
PACKAGES	2,5 l - 1 l
COLOURS	"Patine e velature", "Rilievi"

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Colorificio MP S.r.l.